



Dell Networking S3048-ON

1GbE top-of-rack open networking switch

High density 1000BASE-T switch

The Dell Networking S3048-ON 1000BASE-T Top-of-Rack (ToR) switch is the industry's first 1GbE enterprise switching platform to deliver both an industry hardened OS and support for open networking, providing freedom to run third-party operating systems (OS), such as Cumulus Linux.

This open networking platform is built for high-performance, software-defined data centers and provides the features to run traditional workloads and the flexibility to deploy new workloads such as Hadoop, SDS and Big Data. The S3048-ON offers the flexibility to run OS options optimized for diverse deployment needs on a common hardware platform and architecture.

The S3048-ON features a non-blocking switching architecture coupled with OS9.X software, delivering line-rate L2/L3 features for maximized network performance. The S3048-ON design provides (48) 1000BASE-T ports that support 10MbE/100MbE/1GbE and four 10GbE SFP+ uplinks. Each 10GbE interface can be used as uplinks to the network spine/core, as stack ports to connect up to six units in a stacked configuration, or a combination of both, depending on network architecture and uplink/stack bandwidth requirements.

The S3048-ON incorporates multiple architectural features that optimize data center network flexibility, efficiency and availability, including:

- I/O panel to PSU airflow or PSU to I/O panel airflow for hot/cold aisle environments
- Redundant, hot-swappable power supplies and fans with color coded touch points for ease of identification/removal.
- Dell ReadyRails for efficient installation of the switch into data center cabinets.

The S3048-ON also supports Dell Networking's Embedded Open Automation Framework, which provides advanced network automation and virtualization capabilities for virtual data center environments. Embedded Open Automation Framework is a suite of network management apps that can be used together or independently to provide a network that is flexible, available and manageable while helping to reduce operational expenses.

Key applications

- High-density 1000BASE-T ToR server aggregation in high-performance data centers environments
- Active Fabric™ designs with the S- or Z-Series core switch to create a two tier, 1/10/40GbE data center network architecture
- Enterprise, Web 2.0 and cloud service providers' data center networks for ToR applications
- High-performance SDN/OpenFlow 1.3 enabled with ability to inter-operate with industry standard OpenFlow controllers

Key features

- Four SFP+ 10GbE ports for maximum flexibility and investment protection
- I/O panel to PSU airflow or PSU to I/O panel airflow
- Redundant, hot-swappable power supplies and fans
- Supports ONIE for zero-touch installation of alternate network operating systems
- Open Networking offers choice of OS, such as Dell Networking OS9.X for inherent stability and feature richness, or the flexibility of a third-part OS (such as Cumulus Linux)
- VRF-lite enables sharing of networking infrastructure and provides L3 traffic isolation across tenants (including support for multicast and IPv6 routing)
- Enhanced automation capabilities (puppet agent, REST API extensions)
- Supports jumbo frames for high-end performance in virtualized environments and IP storage/server communication
- Increase VM Mobility region by stretching L2 VLAN within or across two DCs with unique VLT capabilities like Routed VLT, VLT Proxy Gateway
- User port stacking support for up to six units managed as one logical device
- Embedded Open Automation Framework adds VM awareness automated configuration and provisioning capabilities to simplify the management of virtual network environments

1 gigabit Ethernet, open architecture, purpose-built switch for the software-defined era

Specifications: Dell Networking S3048-ON switch

Ordering information

S3048-ON 1000BASE-T

S3048-ON 1000BASE-T, 48 x 1000BASE-T, 4 x SFP+, 1 x AC

PSU, 3 x Fans, IO I/O Panel to PSU Airflow

S3048-ON 1000BASE-T, 48 x 1000BASE-T, 4 x SFP+, 1 x AC

PSU, 3 x Fans,, PSU to I/O Panel Airflow

S3048-ON 1000BASE-T, 48 x 1000BASE-T, 4 x SFP+, 1 x AC

PSU, 3 x Fans, I/O Panel to PSU Airflow, TAA

S3048-ON 1000BASE-T, 48 x 1000BASE-T, 4 x SFP+, 1 x AC

PSU, 3 x Fans, PSU to I/O Panel Airflow, TAA

Redundant power supplies

S3048-ON 1000BASE-T, AC Power Supply, I/O Panel to PSU Airflow

S3048-ON 1000BASE-T, AC Power Supply, PSU to IO I/O Panel Airflow

Fans

S3048-ON 1000BASE-T fan module, I/O Panel to PSU Airflow

S3048-ON 1000BASE-T fan module, PSU to I/O SR4 Panel Airflow

Optics*

Transceiver, SFP, 100BASE-FX, 1310nm wavelength, up to 2km reach

Transceiver, SFP, 1000BASE-T

Transceiver, SFP, 1000BASE-SX, 850nm wavelength, up to 550m reach

Transceiver, SFP, 1000BASE-LX, 1310nm wavelength, up to 10km reach

Transceiver, SFP, 1000BASE-ZX, 1550nm wavelength, up to 80km reach

Transceiver, SFP+, 10GbE, LRM, 1310nm wavelength, up to 220m reach

Transceiver, SFP+, 10GbE, SR, 850nm wavelength, up to 300m reach

Transceiver, SFP+, 10GbE, LR, 1310nm wavelength, up to 10km reach

Transceiver, SFP+, 10GbE, ER, 1550nm wavelength, up to 40km reach

Transceiver, SFP+, 10GbE, ZR, 1550nm wavelength, up to 80km reach

Cables*

Dell Networking cable, SFP+ to SFP+, 10GbE, copper twinax direct attach cable, 0.5m

Dell Networking cable, SFP+ to SFP+, 10GbE, copper twinax direct attach cable, 1m

Dell Networking cable, SFP+ to SFP+, 10GbE, copper twinax direct attach cable, 3m

Dell Networking cable, SFP+ to SFP+, 10GbE, copper twinax direct attach cable, 5m

Dell Networking cable, SFP+ to SFP+, 10GbE, copper twinax direct attach cable, 7m

Dell Networking Cable, SFP+ to SFP+, 10GbE, Active Optical Cable, 15m

Software

Software, Dell Networking OS9.X,

Note: In-field change of airflow direction not supported.

*Ordered separately

Physical

48 line-rate 1000BASE-T ports

4 line-rate 10GbE SFP+ ports

1 RJ45 console/management port with RS232

signaling

Size: 1 RU, 1.71" h x 17.09" w x 12.6" d (4.4 h x 43.4 w x 32.0 cm d)

Weight: 12.8 lbs (5.84 kg) with 1 power supply,

14.8 lbs (6.74kg) with 2 power supplies

ISO 7779 A-weighted sound pressure level: <36 dBA at 78.8°F (26°C)

Power supply: 90–264 VAC 50/60 Hz

1) AC forward airflow

2) AC reverse airflow

Max. thermal output: 290 BTU/h

Max. current draw per system:

<1A at 100/120V VAC <0.5A at 200/240VAC

Max. power consumption: 87W

Typ. power consumption: 65 Watts

Max. operating specifications:

Operating temperature: 32° to 113°F (0° to 45°C)

Operating humidity: 5 to 85% (RH), non-condensing

Operating altitude: 0ft to 10,000ft above sea level

Max. non-operating specifications:

Storage temperature: –40° to 158°F (–40° to 70°C)

Storage humidity: 5 to 95% (RH), non-condensing

Redundancy

Hot swappable redundant power supplies

Hot swappable redundant fans

User port stacking up to 6 units

Performance

MAC addresses: up to 80k

IPv4 routes: 16K

IPv6 routes: 8K (shared CAM space with IPv4)

Switch fabric capacity: 260Gbps (full-duplex)

130 Gbps (half-duplex)

Forwarding capacity: 131 Mpps

Link aggregation: 16 links per group, 128

groups per stack

Queues per port: 8 queues

Layer 2 VLANs: 4K

MSTP : 64 instances

VRF-lite: 64 instances

Line-rate Layer 2 switching: all protocols,

including IPv4 and IPv6

Line-rate Layer 3 routing: IPv4 and IPv6

IPv4 host table size up to 40k max

IPv6 host table size 8K

IPv4 Multicast table size 8K

LAG load balancing: based on Layer 2, IPv4 or

IPv6 headers

Latency 3.7 µsec for 1000BASE-T, ~1.8 µsec

for SFP+

Packet buffer memory: 4MB

CPU memory: 2GB

IEEE compliance

802.1AB LLDP

802.1D Bridging, STP

802.1p L2 Prioritization

802.1Q VLAN Tagging, Double VLAN Tagging,

GVRP

802.1s MSTP

802.1w RSTP

802.1X Network Access Control

802.3ab Gigabit Ethernet (1000BASE-T)

802.3ac Frame Extensions for VLAN Tagging

802.3ad Link Aggregation with LACP

802.3ae 10 Gigabit Ethernet (10GBASE-X) on

optical ports

802.3az Energy Efficient Ethernet (EEE)

802.3u Fast Ethernet (100BASE-TX) on mgmt

ports

802.3x Flow Control

802.3z Gigabit Ethernet (1000BASE-X)

ANSI/TIA-1057 LLDP-MED

Force10 PVST+

MTU 12,000 bytes

RFC and I-D compliance

General Internet protocols

768 UDP

793 TCP

854 Telnet

959 FTP

General IPv4 protocols

791 IPv4

792 ICMP

826 ARP

1027 Proxy ARP

1035 DNS (client)

1042 Ethernet Transmission

1305 NTPv3

1519 CIDR

1542 BOOTP (relay)

1812 Requirements for IPv4 Routers

1918 Address Allocation for Private Internets

2474 Diffserv Field in IPv4 and Ipv6 Headers

2596 Assured Forwarding PHB Group

3164 BSD Syslog

3195 Reliable Delivery for Syslog

3246 Expedited Assured Forwarding

4364 VRF-lite (IPv4 VRF with OSPF, BGP, IS-IS,

and v4 multicast)

5798 VRRP

General IPv6 protocols

1981 Path MTU Discovery Features

2460 Internet Protocol, Version 6 (IPv6)

Specification

2464 Transmission of IPv6 Packets over

Ethernet Networks

2711 IPv6 Router Alert Option

4007 IPv6 Scoped Address Architecture

4213 Basic Transition Mechanisms for IPv6

Hosts and Routers

4291 IPv6 Addressing Architecture

4443 ICMP for IPv6

4861 Neighbor Discovery for IPv6

4862 IPv6 Stateless Address Autoconfiguration

5095 Deprecation of Type 0 Routing Headers

in IPv6

IPv6 Management support (telnet, FTP,

TACACS, RADIUS, SSH, NTP)

VRF-Lite (IPv6 VRF with OSPFv3, BGPv6, and IS-IS)

RIP

1058 RIPv1 2453 RIPv2

OSPF (v2/v3)

1587 NSSA 4552 Authentication/

2154 OSPF Digital Signatures

2328 OSPFv2 OSPFv3

2370 Opaque LSA 5340 OSPF for IPv6

IS-IS

5301 Dynamic hostname exchange mechanism for IS-IS

5302 Domain-wide prefix distribution with two-level IS-IS

5303 Three way handshake for IS-IS point-to-point adjacencies

5308 IS-IS for IPv6

BGP

1997 Communities

2385 MD5

2545 BGP-4 Multiprotocol Extensions for IPv6

Inter-Domain Routing

2439 Route Flap Damping

2796 Route Reflection

2842 Capabilities

2858 Multiprotocol Extensions

2918 Route Refresh

3065 Confederations

4360 Extended Communities

4893 4-byte ASN

5396 4-byte ASN representations



draft-ietf-idr-bgp4-20 BGPv4
draft-michaelson-4byte-as-representation-05
4-byte ASN Representation (partial)
draft-ietf-idr-add-paths-04.txt ADD PATH

Multicast

1112 IGMPv1
2236 IGMPv2
3376 IGMPv3
MSDP
draft-ietf-pim-sm-v2-new-05
PIM-SMw

Network management

1155 SMIv1
1157 SNMPv1
1212 Concise MIB Definitions
1215 SNMP Traps
1493 Bridges MIB

1850 OSPFv2 MIB
1901 Community-Based SNMPv2
2011 IP MIB
2096 IP Forwarding Table MIB
2578 SMIv2
2579 Textual Conventions for SMIv2
2580 Conformance Statements for SMIv2
2618 RADIUS Authentication MIB
2665 Ethernet-Like Interfaces MIB
2674 Extended Bridge MIB
2787 VRRP MIB
2819 RMON MIB (groups 1, 2, 3, 9)
2863 Interfaces MIB
3273 RMON High Capacity MIB
3410 SNMPv3
3411 SNMPv3 Management Framework
3412 Message Processing and Dispatching for
the Simple Network Management Protocol
(SNMP)
3413 SNMP Applications
3414 User-based Security Model (USM) for
SNMPv3
3415 VACM for SNMP
3416 SNMPv2
3417 Transport mappings for SNMP
3418 SNMP MIB

3434 RMON High Capacity Alarm MIB
3584 Coexistence between SNMP v1, v2 and v3
4022 IP MIB
4087 IP Tunnel MIB
4113 UDP MIB
4133 Entity MIB
4292 MIB for IP
4293 MIB for IPv6 Textual Conventions
4502 RMONv2 (groups 1,2,3,9)
5060 PIM MIB
ANSI/TIA-1057 LLDP-MED MIB
Dell_ITA_Rev_1_1 MIB
draft-grant-tacacs-02 TACACS+
draft-ietf-idr-bgp4-mib-06 BGP MIBv1
IEEE 802.1AB LLDP MIB
IEEE 802.1AB LLDP DOT1 MIB
IEEE 802.1AB LLDP DOT3 MIB
sFlow.org sFlowv5
sFlow.org sFlowv5 MIB (version 1.3)
FORCE10-BGP4-V2-MIB Force10 BGP MIB
(draft-ietf-idr-bgp4-mibv2-05)
FORCE10-IF-EXTENSION-MIB
FORCE10-LINKAGG-MIB
FORCE10-COPY-CONFIG-MIB
FORCE10-PRODUCTS-MIB
FORCE10-SS-CHASSIS-MIB
FORCE10-SMI
FORCE10-TC-MIB
FORCE10-TRAP-ALARM-MIB
FORCE10-FORWARDINGPLANE-STATS-MIB
3376 IGMPv3
MSDP
draft-ietf-pim-sm-v2-new-05 PIM-SMw

Regulatory compliance

Safety

UL/CSA 60950-1, Second Edition
EN 60950-1, Second Edition
IEC 60950-1, Second Edition Including All
National Deviations and Group Differences
EN 60825-1 Safety of Laser Products Part 1:
Equipment Classification Requirements and
User's Guide
EN 60825-2 Safety of Laser Products Part
2: Safety of Optical Fibre Communication

Systems
FDA Regulation 21 CFR 1040.10 and 1040.11

Emissions

Australia/New Zealand: AS/NZS CISPR 22:
2006, Class A
Canada: ICES-003, Issue-4, Class A
Europe: EN 55022: 2006+A1:2007 (CISPR 22: 2006),
Class A
Japan: VCCI V3/2009 Class A
USA: FCC CFR 47 Part 15, Subpart B:2011,
Class A

Immunity

EN 300 386 V1.4.1:2008 EMC for Network
Equipment
EN 55024: 1998 + A1: 2001 + A2: 2003
EN 61000-3-2: Harmonic Current Emissions
EN 61000-3-3: Voltage Fluctuations and
Flicker
EN 61000-4-2: ESD
EN 61000-4-3: Radiated Immunity
EN 61000-4-4: EFT
EN 61000-4-5: Surge
EN 61000-4-6: Low Frequency
Conducted Immunity

RoHS

All S Series components are EU RoHS
compliant.

Certifications

Available with US Trade Agreements Act (TAA)
compliance
USGv6 Host and Router Certified on Dell
Networking OS
9.7 and greater
IPv6 Ready for both Host and Router
UCR DoD APL (core and distribution ASLAN
switch)**

Warranty

1 year return to depot



** UC APL certification is contingent upon successful test completion

© 2016 Dell Inc. All rights reserved. Dell and the Dell logo are trademarks of Dell, Inc. All other company names are trademarks of their respective holders. Active Fabric, OS9, and S-Series are trademarks of Dell, Inc. All other company names are trademarks of their respective holders. Information in this document is subject to change without notice. Dell Inc. assumes no responsibility for any errors that may appear in this document.

Learn More at Dell.com/Networking

May 2016 | Version 1.3
Dell_Networking_S3048_ON_Specification_Sheet

